



## Castrol MAGNATEC 20W-50

CLINGING MOLECULES PROTECT FROM THE START

### Description

Up to 75% of engine wear happens while your engine warms up. When the engine stops oils drain off critical engine parts, however Castrol MAGNATEC's intelligent molecules don't. They cling to the engine like a magnet providing an extra layer of protection.

Castrol MAGNATEC's formulation protects from the moment you start, dramatically reducing engine wear\*.

Castrol MAGNATEC. Instant Protection From The Moment You Start.

*\*As tested in the industry Sequence IVA wear test.*

### Application

Castrol MAGNATEC 20W-50 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SP or earlier specification 20W-50 lubricant.

### Advantages

Castrol MAGNATEC's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down
- Are combined with synthetic technology to provide increased protection in high and low temperature applications

## Typical Characteristics

Name	Method	Units	Castrol MAGNATEC 20W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.880
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	18.0
Viscosity, CCS -15C (20W)	ASTM D5293	mPa.s (cP)	6959
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	161
Viscosity Index	ASTM D2270	None	124
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	206.5
Ash, Sulphated	ASTM D874	% wt	0.80

## Product Performance Claims

API SP

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.